

IN THE CLAIMS

Please amend the claim pursuant to 37 C.F.R. § 1.121 (c) as per direction. Applicant submits a marked copy of the changes to the claim attached hereto.

What is claimed:

1. (Currently Amended) A stackable display container for receiving and displaying products therein, comprising:
 - (a) an upstanding front wall having at least one access opening therein, an upstanding back wall and upstanding right and left end walls;
 - (b) with each of the front and back walls being foldably connected to each of the right and left end walls;
 - (c) with a bottom wall comprising a plurality of panels foldably connected to any of said front, back and right and left end walls;
 - (d) with said front, back and right and left end walls being disposed in a rectangular configuration, defining a first pair of opposing upstanding walls and a second pair of opposing upstanding walls;
 - (e) with the bottom wall being at least substantially closed ~~by~~ when the plurality of ~~its~~ panels are folded to define said bottom wall;
 - (f) with ~~a pair of~~ spacer panels foldably connected to the first pair of ~~the~~ opposing upstanding walls of the container and being arranged generally parallel to and spaced inboard of the second pair of opposing upstanding walls and extending from the front upstanding wall to the back upstanding wall of the container;
 - (g) whereby the second pair of ~~the two~~ opposing upstanding walls and their respectively associated spacer panels comprise means defining stacking supports for the container, wherein each said stacking support is thicker than the combined thickness of ~~an~~ any one upstanding wall in the second pair of opposing upstanding walls and its associated spacer panel.

2. (Original) The container of claim 1, wherein the container is free of a top wall defining an open top for the container.
3. (Currently Amended) The container of claim 2, wherein the ~~front wall has at least one access opening therein, is~~ is in communication with said open top and wherein all spacer panels are disposed generally parallel to said right and left end walls.
4. (Currently Amended) The container of claim 1, including a container divider extending between said front and back upstanding walls and being foldably connected to at least one of the two opposing upstanding front and back walls of the container.
5. (Original) The container of claim 1, wherein the spacer panels are foldably connected to the front and back walls of the container and are spaced inboard of the right and left end walls of the container.
6. (Original) The container of claim 1, wherein the front wall is at least substantially comprised of a pair of front wall panels foldably connected together at upper ends thereof.
7. (Original) The container of claim 1, wherein the rear wall is at least substantially comprised of at least pair of rear panels foldably connected together at upper ends thereof.
8. (Original) The container of claim 1, wherein the container is free of a top wall defining an open top for the container, wherein the front wall has at least one access opening therein, in communication with said open top, wherein the spacer panels are foldably connected to the front and back walls of the container and are spaced inboard of the right and left end walls of the container, wherein the front wall is at least substantially comprised of a pair of front wall panels foldably connected together at

upper ends thereof, and wherein the rear wall is at least substantially comprised of at least pair of rear panels foldably connected together at upper ends thereof.

9. (Original) The container of claim 8, wherein including a container divider foldably connected to two opposing walls of the container.
10. (Currently Amended) A stackable display container preassembly for receiving and displaying products therein when fully assembled, comprising:
 - (a) a front wall unit having at least one access opening therein, a back wall unit and right and left end wall units;
 - (b) with each of the front and back wall units being foldably connected to each of the right and left end wall units;
 - (c) with a bottom wall unit comprising a plurality of panels foldably connected to any of said front, back and right and left end wall units;
 - (d) with said front, back and right and left end wall units being adapted to be disposed in a rectangular configuration in the fully assembled condition of the container preassembly, defining a first pair of opposing upstanding wall units and a second pair of opposing upstanding wall units;
 - (e) with the bottom wall unit being adapted to be at least substantially closed ~~by~~ when the plurality of ~~its~~ panels are folded to define a bottom wall when the container preassembly is fully assembled;
 - (f) with ~~a pair of~~ spacer panels foldably connected to the first pair of ~~the~~ opposing upstanding wall units ~~of the container~~ and being adapted to be generally parallel to and spaced inboard of the second pair of opposing upstanding wall units ~~of the container~~ and extending from the front upstanding wall unit to the back upstanding wall unit when the container preassembly is fully assembled;
 - (g) whereby the second of the two opposing wall units and their respectively associated spacer panels comprise means, when the container preassembly is fully assembled, defining stacking supports for the container, wherein each said

stacking support is thicker than the combined thickness of a wall unit and its associated spacer panel.

11. (Original) The container preassembly of claim 10, wherein the container is free of a top wall unit, defining an open top for the container when the container preassembly is fully assembled.
12. (Currently Amended) The container preassembly of claim 11, wherein the ~~front wall unit has at least one~~ access opening ~~therein~~, is adapted to be in communication with said open top when the container preassembly is fully assembled and wherein all said spacer panels are disposed generally parallel to said right and left end walls when the container preassembly is fully assembled.
13. (Currently Amended) The container preassembly of claim 10, including a container divider unit foldably connected to at least one of the ~~two opposing~~ upstanding front and back wall units ~~of the container.~~
14. (Original) The container preassembly of claim 10, wherein the spacer panels are foldably connected to the front and back wall units of the container preassembly and are automatically spaced inboard of the right and left end wall units of the container when the container preassembly is fully assembled.
15. (Currently Amended) A blank for forming a stackable display container for receiving and displaying products therein, when fully assembled, comprising:
 - (a) a primary front wall panel, at least one primary back wall panel and right and left end wall panels;
 - (b) with each of the right and left end wall panels being foldably connected to each of a the front and back wall panels;
 - (c) with a plurality of bottom wall panels foldably connected to any of said front, back and right and left end wall panels;

- (d) with said front, back and right and left end wall panels being adapted to be disposed in a rectangular configuration in the fully assembled condition of the container ~~blank~~, defining a first pair of opposing upstanding wall units and a second pair of opposing upstanding wall units;
 - (e) with a the plurality of bottom wall panels being adapted to be at least substantially closed when ~~by the plurality of its panels~~ folded to define a bottom wall when the container ~~blank~~ is fully assembled;
 - (f) with a secondary front ~~and back~~ wall ~~panels~~ panel foldably connected to the respective primary front and back wall panels ~~panel~~ and a secondary back wall panel foldably connected to the primary back wall panel;
 - (g) with a pair of spacer panels, each spacer panel having a first and second end, wherein said first end is foldably connected at their one ends thereof to one of the secondary front wall panel and secondary back wall ~~panels~~ panel and having a ~~tabs~~ tab is connected to the second end for attachment ~~at their opposite ends~~ to one of the primary front wall panel and primary back wall ~~panels~~ panel and said spacer panels being adapted to be generally parallel to and spaced inboard of right and left wall panels of the container ~~blank~~ when the container ~~blank~~ is fully assembled ~~into a container~~;
 - (h) whereby the right and left end wall panels and spacer panels comprise means, when the container ~~blank~~ is fully assembled, defining stacking supports for the container, wherein each said stacking support is thicker than the combined thickness of an end wall panel and an associated parallel spacer panel.
16. (Original) The container blank of claim 15, wherein the primary and secondary front wall panels have at least one cutout opening therein.
17. (Currently Amended) The container blank of claim 15, including at least one container divider panel foldably connected to at least one of the primary or secondary front or back wall panel.